## Pure Pressure

Pure Pressure by Pure Rinse Systems is a complete power wash & Reverse Osmosis (RO)/Deionization (DI) system in one. The optional DI cartridge further purifies the RO water for the most demanding spot-free cleaning situations. The power wash system takes in the pure water and produces a time saving water pressure of 1000 psi! Both PUMPTEC pumps are mounted on one motor for a compact, flexible design.

The unit moves easily around a job site — it's frame is only 27" wide and fits through the smallest doorways. The large pneumatic wheels allow easy movement & loading. For storage options, the unit can be stowed horizontally or vertically. Also, the top control panel puts the pressure regulator, pressure gauges and water connections within easy access. The lower tray comes in handy for tool, hose and cord storage while easy access to every major component of the system makes maintenance a breeze.



## **FEATURES**

- High Rejection RO membranes remove 99% of tap water impurities
- Triple pre-filtration for excellent membrane and system protection and long service intervals
- High-efficiency dual pump system is designed to maximize membrane life, pure water production rate and system efficiency
- 1000 psi, 1.75 gpm pure water pressure wash system give powerful, spot-free cleaning
- Both pump systems mounted on one motor for space and weight savings, reduced complexity
- Epoxy coated steel frame made with modular components for fast and simple servicing.
- Vibration isolation mounting for quiet, reducedvibration operation
- 115 VAC pumping system
- Easy-to-add deionization cartridge option
- "Safety First" design GFCI on each power cord

## **SPECIFICATIONS**

- Capacity: 3000 gpd (Water @ 77°F)
- Pre-filter: 10 x 4.25", 5µ, Pleated
- Carbon filter: 10 x 4.0" Carbon
- Final filter: 10 x 4.25", 1μ, Depth
- Membranes: Thin Film Composite, High Rejection
- Housing: PVC and Glass-filled Polyester
- DI Cartridge: 4.5 x 20", Mixed Bed
- Pumps: PUMPTEC Models 348-210 (2.8 gpm at 200 psi), 348-130 (1.7 @ 1000)
- Motor: 1 1/2 hp, 115/230 vac, 7.2/3.6 fla, 1.15 SF
- Regulators: PUMPTEC 500, adjustable 0-200 psi and 0-1000 psi
- Gauges: Industrial grade, Glycerine filled, SS bodies
- Size: 31d x 27w x 51"h
- Weight: 230 lbs dry



Pure Rinse Systems, Inc 13915-H Radium Street NW Ramsey, MN 55303 Ph: 763.433.0303

Fax: 764.433.0404 www.purerinse.com